


# PEM-E200VLA

Intel® ATOM™ based Type ETX module with DDR2 SDRAM, VGA, Fast Ethernet, SATA and USB



## FEATURES

- The Intel® ATOM™ N270 and 945GSE platform that provides cost effective solution and technology
- The Intel® platform brings under 10W TDP solution for easy fan-less design
- SATA and IDE interface provide best cost effective functions for market
- Architecture of module and carrier boards speeds up time-to-market of tailor-made equipment
- Support one SODIMM socket and up to 2GB memory size

## GENERAL

Processor	CPU & Package: Intel® ATOM™ N270 1.6GHz in FCBGA package FSB: 533 MHz
Chipset/Core Logic	Intel® 945GSE and ICH7M
System Memory	Up to 2GB DDR2 533 SDRAM on one SODIMM socket
BIOS	AWARD BIOS
Storage Devices	EIDE: Support two EIDE channel with Ultra DMA 100/66/33 SATA: Support two SATA 150 drives
Solid State Disk	N/A
Watchdog Timer	Programmable via software from 1 sec. to 255 min
Expansion Interface	- Two IDE channels - Four PCI devices - ISA Bus - Two COM Ports - One Printer Port - PS/2 Keyboard and Mouse - Line Out, Line In and MIC
Hardware Monitoring	CPU Temperature
Power Requirement	TBA
Dimension	Dimension: 114(L) x 95(W) mm
Environment	Operation Temperature: 0~60 °C Storage Temperature: -20~80 °C Operation Humidity: 5~90%

## ORDERING GUIDE

<b>Standard</b>	PEM-E200VLA Intel® ATOM™ N270, 945GSE platform based ETX module with DDR2 SDRAM, VGA, Fast Ethernet and USB
-----------------	--

\* Specifications are subject to change without notice.

\* Celeron M® and Pentium® M are registered trademarks of Intel Corporation.

\* Other trademarks, logo, brands and company are the property of their respective owners.



## I/O

MIO	Two serial ports (TTL Level)
IrDA	Yes
Ethernet	One Fast Ethernet Controller
Audio	One HDA Audio Codec
USB	Four USB ports
Keyboard & Mouse	PS/2 Keyboard and Mouse

## DISPLAY

Graphic Controller	Intel® 945GSE integrated Graphics Media Accelerator (Intel® GMA 950)
Graphic Memory	Dynamic share system memory up to 224MB (Intel® DVMT 3.0) or static share system memory up to 128MB
Display Interface	- Support CRT, LVDS and TV-out display interfaces - CRT display resolution up to 2048x1536 @ 85Hz refresh



### Portwell, Inc. (Headquarters)

4F, No. 186, Jian-Yi Rd., Chung-Ho City,  
235 Taipei, Taiwan  
Tel: +886-2-77318888  
Fax: +886-2-82271109  
E-mail: info@portwell.com.tw  
http://www.portwell.com.tw

### American Portwell

Fremont CA Tel: +1-510-403-3399  
Norcross GA Tel: +1-678-969-9808  
E-mail: info@portwell.com  
http://www.portwell.com

### Portwell Japan, Inc.

Tokyo Tel: +81-3-5298-8071  
Osaka Tel: +81-6-4791-2201  
E-mail: info@portwell.co.jp  
http://www.portwell.co.jp

### Beijing Portwell

Beijing Tel: +86-10-82701616  
Shanghai Tel: +86-21-3222-0505  
Shenzhen Tel: +86-755-8621-7695  
E-mail: info@portwell.com.cn  
http://www.portwell.com.cn

### Portwell-Laxsons India

Tel: +91-22-2685-9911  
E-mail: info@portwellaxsons.com  
http://www.portwellaxsons.com

### Portwell, B.V.

Tel: +31-252-620790  
E-mail: info@portwell.nl  
http://www.portwell.nl

### Portwell (UK) Ltd.

Tel: +44(0)1235-750760  
E-mail: info@portwell.co.uk  
http://www.portwell.co.uk