
## PCOM-B218VG

Intel<sup>®</sup> Cedar Trail Mobile based Type VI COM Express with DDR3 SDRAM, VGA, LVDS, Gigabit Ethernet, 3Gbps SATA, IDE and USB

204pin DDR3 SODIMM socket



— Intel<sup>®</sup> NM10

Intel<sup>®</sup> Cedar Trail (BGA Type CPU)

## **FEATURES**

- The Intel<sup>®</sup> Atom<sup>™</sup> D2700 2.13GHz / N2800 1.86GHz / N2600 1.6GHz BGA Type CPU
- Support faster I/O interfaces the four PCI Express lanes
- Support two SATA ports include two 3Gbps ports
- Power sharing technology between CPU and Graphics engine to maximize performance
- Support multiple DP/HDMI/DVI functions with two Display Ports

GENERAL	
Processor	CPU: Intel <sup>®</sup> Cedar Trail Mobile Atom <sup>™</sup> D2700 2.13GHz / N2800 1.86GHz / N2600 1.6GHz BGA Socket
Chipset/Core Logic	Intel® NM10
System Memory	Supports DDR3 SDRAM on one SODIMMs, up to 4GB 1067/1333 MHz
BIOS	UEFI BIOS
Storage Devices	SATA: Support two 3Gbps ports
Solid State Disk	N/A
Watchdog Timer	Programmable by embedded controller on board
Expansion Interface	<ul> <li>Four PCI Express lanes (four x1 lanes can be configured to one x4 lane)</li> <li>LPC Interface</li> <li>SMBus/I2C Interface</li> <li>High definition audio interface</li> </ul>
Hardware Monitoring	CPU Temperature
Power Requirement	ТВА
Dimension	Dimension: 95(L) x 95(W) mm
Environment	Operation Temperature: 0~60 °C Storage Temperature: -20~80 °C Operation Humidity: 5~90%

I/O	
MIO	N/A
IrDA	N/A
Ethernet	One Intel <sup>®</sup> 82552V Fast Ethernet Controller
Audio	N/A
USB	Eight USB ports
Keyboard & Mouse	N/A

DISPLAY	
Graphic Controller	Cedar Trail integrated Intel® Graphics Media Accelerator (GMA) 3600/3650 graphics engine to enhance 3D performance for media applications such as high definition 1080p imaging
Graphic Memory	Dynamic share system memory up to 1GB of 2GB system memory (Intel® DVMT 5.0)
Display Interface	- Support multiple DP/HDMI/DVI functions with two Display Ports



Standard PCOM-B218VG Intel® Cedar Trail based Type VI COM Express with DDR3 SDRAM, VGA, LVDS, 10/100 Ethernet, 3Gbps SATA, IDE and USB

\* Specifications are subject to change without notice.

- $^{\ast}$  Celeron M  $^{\otimes}$  and Pentium  $^{\otimes}$  M are registered trademarks of Intel Corporation.
- \* Other trademarks, logo, brands and company are the property of their respective owners.



American Portwell Fremont CA Tel: +1-510-403-3399 Norcross GA Tel: +1-678-969-9808 E-mail: info@portwell.com http://www.portwell.com