


RUBY-9715VG2AR

Intel® Core™ 2 Duo processor based ATX Industrial Mainboard with DDR2 SDRAM, VGA, Dual Gigabit Ethernet, Audio and USB



FEATURES

- Industrial mainboard in ATX form factor supports Intel® Pentium® 4 processor with Hyper-Threading technology, Core™ 2 Duo, Pentium® D and Celeron® D processor in LGA-775 package up to 1066MHz front side bus
- Support DDR2 667/533 SDRAM up to 4GB in dual channel architecture
- Intel® new GMCH integrated graphics engine increases 9% ~ 25% performance of GMA 900 of Intel 915GV
- One PCI Express x16 slot features high-end graphics card connection interface or dual independent displays with ADD2+ media card that provides TV tuner, video capture in and DVI, TV-out
- Six 32-bit PCI expansion slots for most industrial I/O cards
- Dual Gigabit Ethernet ports based on PCI Express x1 interface without sharing bandwidth of PCI expansion bus
- Four ports for SATA RAID controller providing benefits of Intel Matrix Storage Technology RAID 0, 1, 5, 10

ORDERING GUIDE

Standard	RUBY-9715VG2AR Intel® Core™ 2 Duo processor based ATX Industrial Mainboard with DDR2 SDRAM, VGA, Dual Gigabit Ethernet, Audio and USB
-----------------	---

GENERAL

Processor	CPU & Package: Intel® Core™ 2 Duo, Pentium® D, Pentium® 4, Celeron® D processor in LGA-775 package FSB: 1066/800/533MHz
Chipset/Core Logic	Intel® 945G & ICH7R
System Memory	Up to 4GB DDR2 667/533 SDRAM on four 240-pin DIMM sockets
BIOS	Award BIOS
Storage Devices	EIDE: Support two EIDE devices with Ultra DMA 100/66/33 SATA: Support four SATA 300 drives
Solid State Disk	N/A
Watchdog Timer	Programmable via software from 1 sec. to 255 min.
Expansion Interface	- Six 32-bit PCI expansion slots - One PCI Express x16 slot for graphics card, ADD2+ card or PCI Express x1 (general purpose) card - Up to four PCI Express x1 external interface per (project spec.)
Hardware Monitoring	System monitor (fan, temperature, voltage)
Power Requirement	Typical: +5V@2.69A ; +12V@5.37A
Dimension	Dimension : 312.8(L) x 243.8(W) mm; 12.3"(L) x 9.6" (W)
Environment	Operating Temperature: 0 to 55°C Storage Temperature: -20 to 80°C Relative Humidity: 5% to 90%, non-condensing
MTBF	105,889 hrs

I/O

MIO	Two serial (RS232 x1, selectable RS232/422/485 x1) ports, one at rear I/O panel, one parallel, one FDD channel
IrDA	IrDA 1.0
Ethernet	- Dual 10BASE-T/100BASE-TX/1000BASE-T Ethernet - PCI Express x1 interface based Gigabit Ethernet - Dual RJ-45 connectors with two LED indicators at rear I/O panel
Audio	AC'97 2.2 Audio
USB	Eight USB 2.0 ports (Four ports at rear I/O panel; four ports internal)
Keyboard & Mouse	Dual 6-pin mini-DIN connectors at rear I/O panel for PS/2 keyboard/mouse

DISPLAY

Graphic Controller	GMCH integrated Intel® Graphics Media Accelerator 950 (Intel® GMA 950)
Graphic Memory	Dynamic system memory sharing up to 224MB (Intel® DVM T 3.0) or static system memory sharing up to 128MB
Display Interface	Display resolution up to 2048 x 1536