RPC-500NE

19" 4U industrial rack-mount chassis



FEATURE

- 5.25"x3 +3.5"x2 drive bays for RAID 0, 1, 5 & CD-ROM
- Two ball-bearing cooling fans for better ventilation
- Two card retainer positions
- One K/B connector cap included
- One modularized function panel for single (default) and dual (optional) systems
- ATX M/B applicable, especially for big-AT size M/B
- PS/2 redundant power supply installable

WHAT'S NEW



Replaceable function panel

Two modular designed function panels are available for single or dual system display panels. Any OEM project is welcome.

General

Construction	Heavy-duty steel with aluminum front panel	
Drive Bay	External: 5.25"x3 + 3.5" FDD x1	
	Internal: 3.5" HDD x1	
Card Retainer	Two locations for one card retainer	
Cooling Fan	One 12 cm and one 8 cm ball-bearing cooling fans	
Indicator	Power on/off x1, HDD x1	
Switch	Power on/off x1, System reset x1, K/B lock x1	
Air Filter	One replaceable filter	
Connector	One 6-pin PS/2 K/B connector on the front panel with a cap	
Standard Color	Beige, Black	
Dimension	482(W) x 450(D) x 177(H) mm; 19"(W) x 17.7"(D) x 7"(H)	
Weight	Net: 13.5 kg (29.8 lb); Gross: 14.5 kg (32 lb)	
Backplane	PBP-14I: 14-slot ISA backplane PBP-14AC: 14-slot (12xPCI) active PICMG backplane PBP-14A7: 14-slot (7xPCI) active PICMG backplane PBP-14P4: 14-slot (4xPCI) PICMG backplane PBP-13D4: 13-slot dual-system PICMG backplane	

Power Supply (ORION-330A optional)

Maximum Output	330W	
Output Voltage & Current	+5V@30A, +12V@14A, -5V@0.5A, -12V@1A	
Input Voltage	90V ~ 132V, 180V ~ 264V AC Auto-range	
Input Frequency	47 ~ 63 Hz	
Input Current	10A@115V, 5A@230V	
Efficiency	> 70%	
MTBF Reliability	80,000 hrs	
Certification	UL, cUL, TUV, CE, FCC	

Environment

Operating Temperature Range	0 to +40°C
Storage Temperature Range	0 to +70°C
Relative Humidity	5% to 95%, non-condensing

RPC-500NE

19" 4U industrial rack-mount chassis

FEATURE	BENEFITS
A lockable front door with acrylic windows	Good for dust-proof & Running status visible
One power on/off, one system reset and one K/B lock switches inside the lockable door	Avoid accidental reset for better running security
Modularized function panel for one or dual systems	Easy to keep stock and OEM project
Reserve LED holes for redundant power supplies	For installing dual systems and redundant power supplies more easily
Front replaceable air filter	For easy cleaning
One PS/2 K/B connector on the front panel	Convenient to connect to the keyboard
One K/B connector cap	Good for dust-proof for the front accessible K/B connector
Two ball-bearing cooling fans	Better ventilation to provide the system with higher reliability
Enhanced drive bracket to hold 3x5.25"+1x3.5" (or EZ-Kit) and 1x3.5" drives (internal)	For integrating varied systems with higher flexibility
Shock-resistant cushion for the drive bracket	Suitable for installing RAID and CD-ROM drive
Two adjustable positions for hold-down card retainers	For fixing all the cards more flexibly and tightly
Changeable modularized back panel for 14-slot ISA/PICMG backplane or ATX motherboard	Only one minute to change the back panel Easy to change to different backplanes and keep stock
Field replaceable power supply bracket for both normal PS/2 power supply and PS/2 type redundant power supply	Only 3 minutes to change the defective power supply Only 30 seconds to change the defective PSU module

ORDERING GUIDE

RPC-500NE-14P4-330X

19" 4U rack-mount chassis with 14-slot (4xPCI) PICMG backplane and 330W ATX power supply

RPC-500NE-14P4-300IPY

19" 4U rack-mount chassis with 14-slot (4xPCI) PICMG backplane and 330W ATX power supply

RPC-500NE-14A7-330X

19" 4U rack-mount chassis with 14-slot (7xPCI) PICMG backplane and 330W ATX power supply

RPC-500NE-14A7-300IPY

19" 4U rack-mount chassis with 14-slot (7xPCI) PICMG backplane and 300W PFC ATX power supply

RPC-500NE-MX-B4601

19" 4U rack-mount chassis for ATX motherboard with 460 ATX PFC power supply

EZ-Kit

A kit for holding one NB CD-ROM and one NB FDD within an enhanced 3.5" drive bay

ENGINEERING DRAWING

